
Flask-And-Redis Documentation

Release 1.0.0

Igor Davydenko

Jan 21, 2022

Contents

1	Installation	3
2	Usage	5
3	Configuration	7
3.1	REDIS_CLASS	7
3.2	REDIS_URL	8
3.3	Config prefix	8
4	API	9
5	Changelog	11
5.1	1.0.0 (2019-02-18)	11
5.2	0.7 (2016-11-12)	11
5.3	0.6 (2015-01-08)	11
5.4	0.5 (2013-05-10)	11
5.5	0.4 (2012-09-29)	12
5.6	0.3.3 (2012-08-29)	12
5.7	0.3.2 (2012-08-15)	12
5.8	0.3.1 (2012-06-19)	12
5.9	0.3 (2012-05-21)	12
5.10	0.2.1 (2012-03-30)	12
5.11	0.2 (2012-03-30)	12
5.12	0.1 (2012-03-12)	12
6	Authors	13
	Python Module Index	15
	Index	17

Flask-And-Redis provides simple as dead support of [Redis](#) database for [Flask](#) applications. Extension built around beautiful [redis-py](#) library by Andy McCurdy.

- Works on Python 2.7, 3.4+
- BSD licensed
- Latest documentation [on Read the Docs](#)
- Source, issues and pull requests [on GitHub](#)

Note: `Flask-And-Redis` named as is, cause `Flask-Redis` name already [taken](#), but that library didn't match my needs.

CHAPTER 1

Installation

Use `pip` to install Flask-And-Redis to your system or virtual environment:

```
$ pip install Flask-And-Redis
```


CHAPTER 2

Usage

In regular case all you need is importing *Redis* instance and initialize it with app instance, like:

```
from flask import Flask
from flask_redis import Redis

app = Flask(__name__)
redis = Redis(app)
```

But if you use application factories you could use *init_app()* method,

```
redis = Redis()
# The later on
app = create_app('config.cfg')
redis.init_app(app)
```

Also later you can get redis connection from `app.extensions['redis']` dict, where key is config prefix and value is configured redis connection.

CHAPTER 3

Configuration

Flask-And-Redis understands all keyword arguments which should be passed to `redis.Redis` (or `redis.StrictRedis`, when using `redis-py<3`) classes init method. In easiest way all you need is putting

- `REDIS_HOST`
- `REDIS_PORT`
- `REDIS_DB`

to your settings module. Other available settings are:

- `REDIS_PASSWORD`
- `REDIS_SOCKET_TIMEOUT`
- `REDIS_CONNECTION_POOL`
- `REDIS_CHARSET`
- `REDIS_ERRORS`
- `REDIS_DECODE_RESPONSES`
- `REDIS_UNIX_SOCKET_PATH`

Later these values would initialize redis connection and all public methods of connection's instance would be copied to *Redis*. Also connection would be stored in `Redis.connection` attribute and `app.extensions['redis']` dict.

In addition extension has two more configuration options and ability to connect to multiple redis databases.

3.1 REDIS_CLASS

New in version 0.5.

Before 0.5 version only `redis.Redis` connection used. But as times change and `redis.StrictRedis` class grab default status we start to using it as our default connection class.

To change this behavior or even use your own class for redis connection you should pass a class itself or its path to `REDIS_CLASS` setting as:

```
from redis import Redis
REDIS_CLASS = Redis
```

or:

```
REDIS_CLASS = 'redis.Redis'
REDIS_CLASS = 'path.to.module.Redis'
```

Changed in version 1.0.0.

As in `redis==3.0.0` release `StrictRedis` class renamed to `Redis` once again, when you have `redis-py 3` or any further version installed `Flask-And-Redis` will use `redis.Redis` as default value for redis connection class to use. For previous `redis-py` releases `redis.StrictRedis` still be used as default connection class.

3.2 REDIS_URL

New in version 0.2.

Sometimes, your redis settings stored as `redis://... url` (like in Heroku or DotCloud services), so you could to provide just `REDIS_URL` setting and `Flask-And-Redis` auto parsed that value and will configure then valid redis connection.

In case, when `REDIS_URL` provided all appropriate configurations, and other keys are overwritten using their values at the present URI.

3.3 Config prefix

New in version 0.4.

Config prefix allows you to determine the set of configuration variables used to configure `redis.Redis` connection. By default, config prefix `REDIS` would be used.

But when you want to initialize multiple redis connections, you could do this like:

```
from flask import flask
from flask.ext.redis import Redis

app = Flask(__app__)
app.config['REDIS_HOST'] = 'localhost'
app.config['REDIS_PORT'] = 6379
app.config['REDIS_DB'] = 0
redis1 = Redis(app)

app.config['REDIS2_URL'] = 'redis://localhost:6379/1'
redis2 = Redis(app, 'REDIS2')
```

class flask_redis.Redis(*app=None, config_prefix=None*)

Simple as dead support of Redis database for Flask apps.

__init__(*app=None, config_prefix=None*)

Initialize Redis extension for Flask application.

If *app* argument provided then initialize redis connection using application config values.

If no *app* argument provided you should do initialization later with *init_app()* method.

Generally extension expects configuration to be prefixed with REDIS config prefix, to customize things pass different *config_prefix* here or on calling *init_app()* method. For example, if you have URL to Redis in *CACHE_URL* config key, you should pass *config_prefix='CACHE'* to extension.

Parameters

- **app** – flask.Flask application instance.
- **config_prefix** – Config prefix to use. By default: REDIS

connection

Return Redis connection for current app.

get_app()

Get current app from Flask stack to use.

This will allow to ensure which Redis connection to be used when accessing Redis connection public methods via plugin.

init_app(*app, config_prefix=None*)

Actual method to read redis settings from app configuration, initialize Redis connection and copy all public connection methods to current instance.

Parameters

- **app** – flask.Flask application instance.
- **config_prefix** – Config prefix to use. By default: REDIS

5.1 1.0.0 (2019-02-18)

- Drop Python 2.6 & 3.3 support, ensure Python 3.6+ support. Kudos to [jezdez](#) for pull request & implementation
- Support subclasses of the Redis client class. Again kudos to [jezdez](#) for pull request & implementation
- Use `inspect.getfullargspec()` if available. Kudos to [vibiu](#) for pull request & implementation
- Use `redis.Redis` as default connection class, when using `redis-py >= 3`

5.2 0.7 (2016-11-12)

- Improve multiple app support. Kudos to [timothyqiu](#) for pull request & implementation
- Simplify running tests for test application

5.3 0.6 (2015-01-08)

- Python 3 support.
- Move documentation to Read the Docs.
- Refactor example test project to Comments app which shows how to use two Redis databases simultaneously.

5.4 0.5 (2013-05-10)

- Use `redis.StrictRedis` as connection class by default.
- Understands unix socket path in `REDIS_HOST`.

- Updates to README.

5.5 0.4 (2012-09-29)

- Big refactor for *Redis* class. Do not inherit `redis.Redis` class, store active redis connection in `Redis.connection` attribute and `app.extensions['redis']` dict.
- Add support of `config_prefix` keyword argument for *Redis* or `init_app()` methods.
- Support multiple redis connections in test application.

5.6 0.3.3 (2012-08-29)

- Fix problem while parsing `REDIS_URL` value, strip unnecessary slashes from database path (like `redis://localhost:6379/12/`).

5.7 0.3.2 (2012-08-15)

- Added `redis` as install requirement in `setup.py`.

5.8 0.3.1 (2012-06-19)

- Move from `flask_redis` package to python module.
- Little improvements for storing `_flask_app` attribute to *Redis* instance.

5.9 0.3 (2012-05-21)

- Implement `init_app()` method.

5.10 0.2.1 (2012-03-30)

- Convert `REDIS_PORT` to an `int` instance.

5.11 0.2 (2012-03-30)

- Added support of `REDIS_URL` setting. By default, *Redis* will try to guess host, port, user, password and db settings from that value.

5.12 0.1 (2012-03-12)

- Initial release.

CHAPTER 6

Authors

- Igor Davydenko (original idea & code)
- Lexo Charles
- Hidetaka Yamashita
- Timothy Qiu
- vibiu
- Jannis Leidel

f

`flask_redis`, 9

Symbols

`__init__()` (*flask_redis.Redis method*), 9

C

`connection` (*flask_redis.Redis attribute*), 9

F

`flask_redis` (*module*), 9

G

`get_app()` (*flask_redis.Redis method*), 9

I

`init_app()` (*flask_redis.Redis method*), 9

R

`Redis` (*class in flask_redis*), 9